



Combustion Control Equipment | Temperature Limit and Supervisory Switches | **Temperature Limit Switches, Indicating**

Hybrid Control/Limit Model Option

Product Description

Hybrid Control/Limit Model Option

PM	6	Z	-	Z	Z	Z	Z	-	L	Z	J	A	-	ZZ
I	II	III		IV	V	VI	VII		VIII	IX	X	XI		XII

I	PM - Series Model Designation
II	DIN Panel Size 6 = 1/16 DIN 8 = 1/8 DIN Vertical 9 = 1/8 DIN Horizontal 4 = 1/4 DIN
III	Unit Primary Function C = Control R = Ramping Control X = Any letter (Other than L, M or D) - designates custom Control firmware.
IV	Voltage and Digital I/O Options 1 = HV 100-240 Vac no Digital I/O 2 = HV 100-240 Vac two Digital I/O 3 = LV 12 Vdc/24-28 Vac/dc no Digital I/O 4 = LV 12 Vdc/24-28 Vac/dc two Digital I/O
V	Output 1 Options A = None C = Switched DC E = Mechanical Relay Form C - 5 Amps F = Universal Process Output K = Solid State Relay - 0.5 Amp
VI	Output 2 Options A = None C = Switched DC H = No-Arc Relay output 15 Amps J = Mechanical Relay Form A - 5 Amps K = Solid State Relay - 0.5 Amp



Member of the FM Global Group

VII	<p>Communications Options PM6 only offers options A and 1.</p> <p>A = None B = Bluetooth¹ C = 6 Digital I/O</p> <p>D = 6 Digital I/O with EIA 485 Modbus RTU Communications 1 = 485 Modbus RTU Communications</p> <p>E = 485 Modbus RTU Communications with Bluetooth¹ 2 = RS232 or 485 Modbus RTU Communications</p> <p>F = RS232 or 485 Modbus RTU Communications with Bluetooth¹ 3 = Ethernet</p> <p>G = Ethernet/IP Communications with Bluetooth¹ 5 = Devicenet Communications</p> <p>H = Devicenet Communications with Bluetooth¹ 6 = Profibus Communications</p> <p>J = Profibus Communications with Bluetooth¹ 7 = Can-Bus Communications</p> <p>K = Can-Bus Communications with Bluetooth¹</p> <p>X = Any letter or number - future communications options</p> <p>¹NOTE: Bluetooth only available on PM6 models.</p>
VIII	<p>Auxiliary Control Functions</p> <p>L = Integrated Limit Controller with universal input. M = Integrated Limit Controller with thermistor input. D = Integrated Limit with custom firmware defaults.</p>
IX	<p>Output 3 Options</p> <p>A = None C = Switched DC</p> <p>E = Mechanical Relay Form C - 5 Amps</p>
X	<p>Output 4 (Limit Output) Options</p> <p>J = Mechanical Relay Form A - 5 Amps</p>
XI	<p>Firmware options</p> <p>A = Standard Firmware, input 1 not isolated B = PM Express Firmware - Series 94 emulation, input 1 not isolated C = Enhanced Firmware, input 1 not isolated D = Standard firmware, isolated input 1 F = Enhanced firmware, isolated input 1</p> <p>S = Slave - Used to download customer configurations to other PM models in field</p> <p>G = PM Touch Panel LED Display, Standard firmware, Isolated input 1, 2 sensors H = PM Touch Panel LED Display, Express Version, Isolated input 1, 2 sensors P = PM6 Plus Touch Panel Display, Standard firmware, isolated input 1 and 2 V = PM6 Touch Panel Display, Enhanced firmware, isolated input 1 and 2</p>
XII	<p>Customer firmware/Overlay Options</p> <p>AA = Standard Product</p> <p>XX = Any two letters or numbers indicating custom non-critical options.</p>



Details

Category	Temperature Limit Switches, Indicating
Class of Work	3545 - Sw, Temp & Supv
Certification Type	FM Approved
Listing Country	United States of America

Company

Watlow Electric Manufacturing Company
1241 Bundy Blvd, Box 5580,
Winona, Minnesota 55987
United States of America
<http://watlow.com>